

positioning tilt-in-space chair

Optimum

1400 Series

FOCUSED ON WHAT MATTERS



SPECIALTY
HEALTHCARE
SEATING



OPTIMUM 1400

Shown in standard configuration
with optional Silvertex Turquoise vinyl



COMFORT AND POSITIONING

Optimum

positioning tilt-in-space chair

Contoured articulated headrest (code AB-14)
for better head and neck support
and alignment

PRE-CURE® seat cushion composed
of high resilience foam
and visco gel memory foam

This cushion is standard and is designed
to help prevent pressure ulcers

Adjustable elbow supports
(code AB-13)

Removable backrest
upper section with
adjustable side wings
(code AB-17)
Comfortable, safe
and ideal for resting

Gas-cylinder assisted tilt,
backrest reclining and elevating
leg and foot rest

The backrest cylinder is
equipped with an adjustable
blocking ring to limit reclining
between 102° and 145°

Mobility Group 24" wheels
(code 1P-02)



Backrest is built
on elastic bands
for exceptional comfort

A solution for prolonged sitting...


- + Improves user comfort as the best alternative between a bed and an armchair.
- + Meets the patient's positioning needs.
- + Ensures safe transfers both independently and with the help of a patient lift.
- + Makes it easier for caregivers to reduce the risk of accidents at work.
- + Reduces patient care costs.

FACTORY CONFIGURATION

Standard	Comfort Group AB-17	Positioning Group AB-14
Chair configuration with removable upper backrest	Chair configuration with removable upper backrest and adjustable side wings	Configuration with contoured-articulated headrest, replaces standard upper backrest

ACCESSORY GROUPS

ITEM	DESCRIPTION
1P-04	UTILITY group: activity table + cervical support
1P-02	MOBILITY group 24" (60 cm) wheels with brakes and anti-tippers
1P-06	UTILITY AND MOBILITY GROUPS COMBINATION



AA-10




AB-12



AB-13



AB-14-R



AB-17



AB-18-R

ACCESSORIES

ITEM	DESCRIPTION
AA-03	Lowered seat 2" (5 cm)
AA-04	Seat pan for specialized cushions
AA-06	Side bolsters 1" (2.5 cm)
AA-10	PRE-CURE® PRO cushion (option AA-04 required)
AB-04	Adjustable lateral trunk support 4" (10 cm)
AB-05	Adjustable lateral trunk support 6" (15 cm)
AB-06	Adjustable shoulder support
AB-07	Cervical support
AB-08	Contoured headrest
AB-09	Adjustable tension backrest
AB-12	Adjustable structural lateral supports
AB-13	Adjustable elbow supports (pair)
AB-14-R	Additional contoured and articulated headrest
AB-17-R	Adjustable wings for upper section of backrest
AB-18-R	Additional upper backrest
AC-01	Opaque activity tray
AC-03	Activity tray with Lexan window
AC-04	Padded tray cover
AC-07	Hemiplegic armrest
AD-01	Padded footboard cover
AD-02	Lateral leg protector
AD-03	Footboard extension 2" (5 cm)
AD-04	Elevating footrest cushion
AD-05	Extra-large footboard
AE-01	Adjustable IV pole
AE-02	Catheter drainage bag hook
RA-03	Lateral tray straps
RA-03A	Wrap-around tray strap
RA-19	Universal perineal abductor kit with black fixing mat

Vinyl upholstery standard. Crypton fabric and Silvertex vinyl available as options.
Meets CA TB117-2013 fire standards.

TECHNICAL SPECIFICATIONS

	1400-18	1400-20	1400-22	1400-24
Min. length, upright	38" / 97 cm			
Max. length, reclined	68" / 173 cm			
Overall width	23 1/2" / 60 cm	26 1/2" / 67 cm	29 1/4" / 74 cm	29 1/4" / 74 cm
Overall width (MOBILITY PACKAGE)	27 1/2" / 70 cm	32 1/2" / 83 cm	35 3/4" / 91 cm	35 3/4" / 91 cm
Seat-to-floor height	20 1/2" / 52 cm			
Height with upper backrest	50" / 127 cm			
Height without upper backrest	39 3/4" / 101 cm			
Seat width	17 3/4" / 45 cm	20 1/2" / 52 cm	22" / 56 cm	24" / 61 cm
Seat depth	15 1/2" to 19" / 39 to 48 cm			
Seat back height	32" / 81 cm			
Lower backrest height	20" / 51 cm			
Backrest reclining angle	102 to 145 degrees			
Seat tilt angle	0 to 30 degrees			
Set/leg rest angle	80 to 132 degrees			
Armrest height	0 to 8 1/2" / 0 to 22 cm • 0 to 11" / 0 to 28 cm with option AA-03			
Total weight without accessories	85 lbs. / 39 kg	90 lbs. / 41 kg	95 lbs. / 43 kg	
Maximum weight capacity	300 lbs. / 136 kg		450 lbs. / 204 kg	

Please note that the technical specifications are subject to change without notice.