

The Hoyer® Presence® lift has been engineered and designed to handle almost any resident-handling task. Along with the Stature lift, the Presence can lift residents from the floor as well accommodate transfers to higher surfaces. The 500 lbs safe working load and greater spatial area make this lift a perfect fit for larger residents. The Presence comes standard with a powered base and is available with a scale option.



Smart Monitor

The unique Smart Monitor control box is programmable and will accurately record and display vital lift utilization and service data. An easy to read LCD display provides the valuable information at the touch of a button.



Interchangeable Cradle Bars

Part of the restriction of using certain lifts are the slings that you can use on the product. The Presence however, gives you a choice of sling systems.



Low Leg Option

The Low Leg Option Kit for the Hoyer Presence lift is designed to fit under beds, stretchers, and other furnishings with low clearance. Total leg height is 2.4". Part #: 39001310



Foot Pad

Ergonomic foot pad to assist with initiating movement.

SPECIFICATION	IMPERIAL	METRIC
Safe Working Load	500 lbs	227 kgs
Maximum Overall Length	57.5"	1460 mm
Minimum Overall Length	55.1"	1400 mm
Maximum Overall Height	81.3"	2065 mm
Minimum Overall Height	57.5"	1460 mm
Spreader Bar Maximum Height	75.2"	1910 mm
Spreader Bar Minimum Height	16.9"	430 mm
Height at Maximum Reach	51.5"	1310 mm
Reach at Maximum Height	25.6"	650 mm
Reach at Minimum Height	15.7"	400 mm
Maximum Reach	36.6"	930 mm
Turning Radius	64.2"	1630 mm
Legs Open - Internal Width	40.1"	1020 mm
Legs Closed - External Width	26.4"	670 mm
Front Twin Casters	4.0"	100 mm
Rear Braked Casters	4.0"	100 mm
Overall Height of Legs	4.7"	120 mm
With Low Leg Option	2.4"	60 mm
Ground Clearance	1.4"	35 mm

* Reach = center of spreader bar to the front of the mast

4 POINT POSITION CRADLE (measurement to top of location pins)

Cradle Max. Height	61.0"	1550 mm
Cradle Min. Height (usable)	15.4"	390 mm

WEIGHT	IMPERIAL	METRIC
Total	88.0 lbs	40 kgs

ELECTRIC SHOCK PROTECTION

Charger – Class II
Lift – Internal power source

DEGREE OF SHOCK PROTECTION

Charger – Type B
Lift – Type B
Intended operating environment: >+5°C <+40°C
Outside this environment functionality and safety may be compromised

ELECTRICAL SPECIFICATIONS

Battery – 24vDC rechargeable sealed lead acid type
3.2A hours
Charger rated input – 100-240V AC 24 VDC 50/60Hz
Charger rated output – 29.5 VDC, Max. 19 W